

## ASSEMBLY INSTRUCTIONS

## Farfalle Large Semi-Flush Mount

Item # JN4405

**NOTICE:**

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

**TOOLS REQUIRED (NOT INCLUDED):**

Phillips Screwdriver


### Slotted Screwdriver

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove mounting plate **(B)** from canopy **(G)** by removing collar ring **(H)**.
3. Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)**.
4. Remove swivel ball **(F)** from rod **(O)**.
5. Let collar ring **(H)** and canopy **(G)** pass through rod **(O)**, then secure swivel ball **(F)** to rod **(O)**.
6. Hang fixture swivel ball **(F)** to the center of mounting plate **(B)** and secure with set screw **(D)** with provided wrench **(E)**.
7. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut **(A)**.


**NOTE:** It is imperative that the fixture is grounded.

8. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut **(A)**.
9. Connect fixture hot wire (black) to the supply hot wire (usually black) using wire nut **(A)**.

**CAUTION:** Do not reverse the hot and neutral connections.



## ASSEMBLY INSTRUCTIONS



## Farfalle Large Semi-Flush Mount

Item # JN4405

### NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

10. Make sure all wire connections are tight, then carefully tuck into the junction box.
11. Install canopy (G) to mounting plate (B) and secure with collar ring (H).
12. Install light bulbs into the sockets.
13. Install top shade (J) to nipple (I) and secure with metal ring (K).
14. Install bottom shade (L) to nipple (I) and secure with hex nut (P) using provided wrench (Q).
15. Install metal cap (M) to nipple (I) and secure with finial (N).

**CARE INSTRUCTIONS:** Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.